

AP Product Summary



Scenario AP	Model	Wireless Data Rate	Max Client per AP	Smart Antenna	Antenna	IEEE 802			2.4GHz	5GHz	Port		POE Ports		VAP	Pre-AX/C-link/Air-Recorder
						11ax	11ac Wave1	11ac Wave2			GE	SFP	input	output		
Indoor AP	AP840-I	5.2Gbps	384	*	6X6MU-MIMO	*	*	*	*	*	3	N/A	2	N/A	*	
	AP730-L	2.133Gbps	768	*	2x2 MU-MIMO			*	*	*	1	N/A	1	N/A	*	*
	AP720-I	1.267Gbps	256	*	2x2 MU-MIMO			*	*	*	2	N/A	1	N/A	*	*
	AP720-L	1.167Gbps	256	N/A	2x2 MU-MIMO			*	*	*	1	N/A	1	N/A		
	AP710	1.167Gbps	256	N/A	2x2 MIMO (2.4G) 2X2 MIMO (5G)		*		*	*	1	N/A	1	N/A		
	AP210-L	300Mbps	128	N/A	2x2				*					1	N/A	
Wall AP	AP130(w2)v2	1.167Gbps	32	N/A	2x2 MU-MIMO			*	*	*	1*GE UP 4*GE LAN	N/A	1	N/A		
	AP130(L)	1.167Gbps	32	N/A	2x2 MIMO		*		*	*	1*GE UP 4*FE LAN	N/A	1	N/A		
	AP110-L	300Mbps	32	N/A	2x2				*					1	N/A	
Outdoor AP	AP630(IDA2)	2.533Gbps	256	N/A	4X4 MU-MIMO Support External			*	*	*	2	1	1	N/A		
	AP630(IODA)	1.750Gbps	256	N/A	3X3 MIMO Support External		*		*	*	2	1	1	1		
	AP630(CD)	1.167Gbps	256	N/A	2X2 MIMO		*		*	*	2	1	1	N/A		